

Statement of Quantities

Item No	Code	Description	UOM	Quantity
1	01-21.16.01	ALLOWANCE FOR TREE REMOVAL, TRIMMING/ REPLACEMENT AND DISPOSAL - SEE PROJECT SPECIAL PROVISIONS	Lump-Sum	1
2	01-52.13	TEMPORARY OFFICE FACILITIES	Lump-Sum	1
3	2-1.2a	REMOVE 6" CONCRETE CURB AND/OR GUTTER	Linear Foot/Feet	1,001
4	2-1.4	REMOVE SIDEWALK ACCESSIBILITY CONCRETE CURB RAMP	Square Foot/Feet	1,590
5	2-2.1	REMOVE CONCRETE SIDEWALK	Square Foot/Feet	4,924
6	2-2.2	REMOVE CONCRETE DRIVEWAY PAVING	Square Foot/Feet	2,728
7	2-3.4	REMOVE CONCRETE STREET INTERSECTION GUTTER (CROSSPAN) AND/OR VALLEY GUTTER: CROSSPANS AT MISSISSIPPI & ONEIDA INTERSECTION	Square Foot/Feet	661
8	2-3.5	REMOVE CONCRETE STREET PAVING: EXISTING BUS PAD ON MISSISSIPPI AVE	Square Foot/Feet	28
9	2-11.1a	REMOVE EXISTING 8" SANITARY SEWER PIPE: PVC	Linear Foot/Feet	28
10	2-17.3	REMOVE AND REPLACE/RELOCATE SIGN: REMOVE AND RESET SIGN POST	Each	7
11	2-22	REMOVE PARKING LOT TRENCH DRAIN: REMOVE SIDEWALK TRENCH DRAIN	Linear Foot/Feet	5
12	02-22.13	VIBRATION ASSESSMENT	Lump-Sum	1
13	2-24	REMOVE AND REPLACE BUS STOP: TEMPORARILY RELOCATE MISSISSIPPI BUS STOP	Each	1
14	3-2	HAULING OF CONTAMINATED MATERIALS TO DENVER/ARAPAHOE DISPOSAL SITE (DADS)*LICENSED PER D.R.M.C. 48-62	Ton	100
15	3-4b	GEOTEXTILE: TENSAR TRIAX TX7 GEOGRID (OR APPROVED EQUAL)	Square Foot/Feet	55,958
16	3-7a	HEALTH & SAFETY PLAN	Lump-Sum	1
17	3-7b	MATERIAL MANAGEMENT PLAN	Lump-Sum	1
18	5-7	CONTROLLED LOW STRENGTH MATERIALS (CLSM): TO BE USED AT THE DIRECTION OF THE PROJECT MANAGER OR PROJECT INSPECTOR	Cubic Yard	100
19	5-8	CRUSHED GRAVEL BASE COURSE (CDOT CLASS 6 ROAD BASE): ASPHALT PAVING - Assumed unit weight 120 LB/CUFT	Ton	1,679
20	8-1.1b	6" DIP AWWA C151, CLASS 50 WATER LINE: HYDRANT LINES	Linear Foot/Feet	91
21	8-1.1c	8" DIP AWWA C151, CLASS 50 WATER LINE: 8" MAIN AND SERVICE	Linear Foot/Feet	66
22	8-1.1c	8" DIP AWWA C151, CLASS 50 WATER LINE: WITH 18" STEEL CASING	Linear Foot/Feet	22
23	8-1.2b	INSTALL 6" WATER VALVE: On Hydrant lines	Each	3
24	8-1.2c	INSTALL 8" WATER VALVE	Each	2
25	8-1.5a	LEAD SERVICE LINE REPLACEMENT, <2" ID	Linear Foot/Feet	271
26	8-3	RESET OR INSTALL FIRE HYDRANT ASSEMBLY	Each	3
27	8-4	REMOVE EXISTING WATER LINE: ABANDONED FAIRMOUNT WATER	Linear Foot/Feet	20

Statement of Quantities

Item No	Code	Description	UOM	Quantity
28	8-4	REMOVE EXISTING WATER LINE: HYDRANT LINE	Linear Foot/Feet	91
29	8-4	REMOVE EXISTING WATER LINE: WATER MAIN	Linear Foot/Feet	88
30	12-1.1	6" CURB AND GUTTER 2' PAN (CDOT T2, IIB)	Linear Foot/Feet	994
31	12-1.8	SIDEWALK ACCESSIBILITY CONCRETE CURB RAMP	Square Foot/Feet	1,398
32	12-2.1	CONCRETE SIDEWALK	Square Foot/Feet	4,673
33	12-5.1	CONCRETE DRIVEWAY PAVING	Square Foot/Feet	2,728
34	12-5.3	CONCRETE BUS PAD	Square Foot/Feet	697
35	16-1	SECURITY FENCE: TEMPORARY 6' CHAINLINK FENCE - TREE PROTECTION	Linear Foot/Feet	1,215
36	20-2bf	*** NOTE: UOM = SY-IN *** ASPHALT SURFACE COURSE, SX, RAP 20%, N=75, 76-28	Other	14,922
37	20-3be	*** NOTE: UOM = SY-IN *** ASPHALT BASE COURSE, S, RAP 20%, N=75, 64-22: INCLUDE UP TO 4 MOBILIZATIONS	Other	59,434
38	33-05.26.01	EXISTING UTILITY LOCATION/COORDINATION/RELOCATION AND/OR ADJUSTMENT	Lump-Sum	1
39	34-2.3e	18" DIAMETER C-76 RCP, CLASS III	Linear Foot/Feet	36
40	34-2.3g	24" DIAMETER C-76 RCP, CLASS III	Linear Foot/Feet	104
41	34-2.3i	30" DIAMETER C-76 RCP, CLASS III	Linear Foot/Feet	44
42	34-2.3k	36" DIAMETER C-76 RCP, CLASS III	Linear Foot/Feet	155
43	34-2.3n	48" DIAMETER C-76 RCP, CLASS III	Linear Foot/Feet	22
44	34-6.2	PRECAST RCBC (SPECIAL SIZE AND/OR DESIGN): 8'X7'	Linear Foot/Feet	1,234
45	34-7.1a	8" DIAMETER PVC PIPE: SANITARY PIPE	Linear Foot/Feet	496
46	34-12.1a	4' DIAMETER PRECAST MANHOLE WITH TYPE A BASE & CONCENTRIC CONE: SANITARY MANHOLES	Each	1
47	34-12.1c	4' DIAMETER PRECAST MANHOLE WITH TYPE C BASE & CONCENTRIC CONE: 4' MANHOLE ACCESS TO BOX CULVERT	Each	4
48	34-12.3c	6' DIAMETER PRECAST MANHOLE WITH TYPE C BASE & CONCENTRIC CONE: STORM MANHOLES	Each	2
49	34-12.7	CAST-IN-PLACE SPECIAL STRUCTURE: COLLAR CLOSURE AT BEND	Each	1
50	34-12.7	CAST-IN-PLACE SPECIAL STRUCTURE: REINFORCED CONCRETE BOX BENDS (8'X7')	Each	3
51	34-12.10	8' DIAMETER PRECAST MANHOLE WITH TYPE C BASE AND CONCENTRIC OPENING FLAT TOP: STORM MANHOLE	Each	1
52	34-13.1a	8" PIPE OUTSIDE DROP	Each	1
53	34-15.2	RECONNECT SANITARY SEWER SERVICES (TAPS) (OPEN CUT): 6690 Mississippi Ave	Each	1
54	34-15.3	UTILITY EXPLORATORY INVESTIGATION	Each	15

Statement of Quantities

Item No	Code	Description	UOM	Quantity
55	34-16.1c	#14 INLET (L=12')	Each	3
56	34-16.3a	DOUBLE #16 INLET WITH OPEN THROAT	Each	3
57	34-16.4a	TRIPLE #16 INLET WITH OPEN THROAT	Each	8
58	34-16.5	PARKING LOT TRENCH DRAIN: SIDEWALK TRENCH DRAIN	Each	1
59	34-17.30	SANITARY BYPASS PUMPING	Lump-Sum	1
60	40-4b	RELOCATE EXISTING SPRINKLER LINE	Linear Foot/Feet	50
61	41-1	TRAFFIC CONTROL	Lump-Sum	1
62	43-1b	STORM WATER MANAGEMENT (SCENARIO 2) SEE SCS 23.0	Lump-Sum	1
63	44-1	DEWATERING	Lump-Sum	1
64	45-2	QUALITY CONTROL TESTING	Lump-Sum	1
65	46-2	EPOXY PAVEMENT MARKING: Striping	Square Foot/Feet	183
66	46-3	THERMOPLASTIC PAVEMENT MARKING: Cross Walk and Stop Bars	Square Foot/Feet	570
67	47-1	CONSTRUCTION SURVEYING	Lump-Sum	1
68	50-1	MOBILIZATION	Lump-Sum	1